

## SERVO SYSTEM

### FEATURES

- High energy saving
- Better Molding Stability
- Quick response
- Quiet & low noise
- Reliable holding pressure
- Slow Oil temperature rise
- Power saving up to 60% on renovated machines.
- Driver Rated Power up-to 55KW
- Rated Current 22A to 81A



Note: We reserve the right to cancel or change the above specific model without any prior notice.

## SERVO SYSTEM

## SPECIFICATIONS

MODEL	140032-S	140040-S	140050-S	140063-S	140080-S	1400100-S	1400125-S	1400160-S
Aruchi Driver	NAS4G32/ 58XS	NAS4G32/ 58XS	NAS4G45/ 81X	NAS4G45/ 81X	NAS4G60/ 108X	NAS4G75/ 135X	NAS4G90/ 162X	NAS4G110/ 198X
Driver Rated Power	16KW	16KW	22.5KW	30KW	30KW	37.5KW	45KW	55KW
Current	32A	32A	45A	60A	60A	75A	90A	110A
Maximum Current	58A FOR 10SECS	58A FOR 10SECS	108A FOR 10SECS	108A FOR 10SECS	108A FOR 10SECS	135A FOR 10SECS	162A FOR 10SECS	198A FOR 10SECS
Aruchi Motor	190 - 4E57/ 20 - 120X NG2	190 - 4E80/ 20 - 160X NG2	190 - 4E93/ 20 - 185X NG2	230 - 4E117/ 20 - 235X NG2	230 - 4E143/ 17 - 290X NG2	230 - 4E191/ 17 - 385X NG2	230 - 4E223/ 17 - 445X NG2	230 - 4E269/ 17 - 555X NG2
Motor Rated Torque	57NM	80NM	93NM	117NM	143NM	191NM	223NM	269NM
Maximum Torque	120MM	160MM	185MM	235MM	290MM	385MM	445MM	555MM
Motor Rated Speed	2000 - 2700	2000 - 2700	2000 - 2700	2000 - 2700	1700 - 2200	1700 - 2200	1700 - 2200	1700 - 2200
Motor Power	12KW	17KW	20KW	25KW	25KW	34KW	40KW	48KW
Rated Current	22A	29A	33A	48A	46A	61A	70A	81A
Pump Displacement	32CC/r	40CC/r	50CC/r	63CC/r	80CC/r	100CC/r	125CC/r	160CC/r
Flow	80 Lpm	100 Lpm	125 Lpm	157 Lpm	160 Lpm	200 Lpm	250 Lpm	320 Lpm

Note: We reserve the right to cancel or change the above specific model without any prior notice.